

# ProLite B2209HDS-1

This attractive, slim bezel 22" LCD display features the latest 'triple' input configuration of HDMI, DVI and Analogue for ensured compatibility. The B2209HDS continues the trend of true 1920 x 1080, 16:9 format panels in desktop displays. Featuring an incredible 2msec response time and 20,000:1 Advanced Contrast Ratio the experience for gamers is enhanced and depth of colour in Video assured. ProLite B2209HDS is height adjustable and features PIVOT function.



Panel	TN
Diagonal	22"
Display area h x w	268.6 x 447.5 mm; 10.6" x 18.8"
Response time	2 ms
Contrast	20 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	300 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
HDCP	yes
Output connector	headphone connector
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, stand-base, screw for stand fixing, quick start guide, safety guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu /Select Button, + /Volume Button (+), - / Eco Button (-), Auto)
User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (gamma, colour temperature), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, HDMI audio, information), volume, auto adjust
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Ergonomics	CE, TÜV-GS, TCO '03
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	41 W typical; max. 1 W in Power management mode
Power management	VESA DPMS
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Height adjustment	110 mm
Rotation (pivot function)	90°
Swivel Stand	340°; 170° left; 170° right
Tilt angle	20° up
Dimensions w x h x d	513 x 399.5 (509.5) x 249.5 mm
Weight	6.3 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.